



Computer Vision

Thermal Imaging and Infrared

10 April 2018

Developed by Klaas Dijkstra & Henry van Arem

Copyright © 2001 – 2018 by
NHL Stenden Hogeschool and Van de Loosdrecht Machine Vision BV
All rights reserved

j.van.de.loosdrecht@nhl.nl, jaap@vdlmv.nl

Infrared Theory

Electromagnetic spectrum

Color Temperature


Emissivity

BlackBody

27-Aug-18

Thermal Imaging and Infrared

2







Energy flows

“Every object absorbs energy and will emit the same amount of energy when objects temperature is in balance”


- Convection
- Conduction
- Radiation
 - Absorption / Emission (Temperature)
 - Reflection
 - Transmission (not discussed)

27-Aug-18
Thermal Imaging and Infrared
4





Infrared signals setup



The diagram illustrates an infrared setup. On the left is a thermal camera labeled 'FLIR A20'. On the right is a green rectangular object. Three arrows point from the object towards the camera: the top arrow is labeled '3' and points to the camera; the middle arrow is labeled '2' and points to the object; the bottom arrow is labeled '1' and points to the object. A legend below the diagram defines the numbers: 1 Reflection, 2 Object Temperature, 3 Atmosphere.

1 Reflection
2 Object Temperature
3 Atmosphere

27-Aug-18 Thermal Imaging and Infrared 9


BlackBody

A theoretical *blackbody* absorbs all radiation of all wavelengths, it does not reflect any radiation.

Emissivity = 1


An eye is a practical example of a blackbody
(It is not a perfect *blackbody*, but a *graybody*)

Higher emissivity is better



The top image is a diagram of a blackbody, represented as a gray circle with a black outline, set against a blue background. The bottom image is a photograph of a human eye, showing the iris and pupil, which is used as a practical example of a blackbody.

27-Aug-18 Thermal Imaging and Infrared 10



IR Camera Parameters

Object Emissivity:
A value between the 0 and 1 for calculating the temperature

27-Aug-18
Thermal Imaging and Infrared
12

Retrieve Images

5 different type of images.

- **Absolute Image Pixels (IntImage)**
 - Absolute values from the sensor
- **Object Signal Pixels (FloatImage)**
 - Corrected values for influence by atmosphere and for Reflected Temperature.
- **Temperature (FloatImage)**
 - Temperatures in Kelvin
- **Relative Temperature (IntImage)**
 - Temperature relative to the high and lower scale limit
- **Relative Temperature Image Lut (IntImage)**
 - Image based on a Lut

27-Aug-18

Thermal Imaging and Infrared

13

Emissivity Calculation

3 ways of determining the emissivity of an object

- Look the material up in an emissivity table
- Change the emissivity value until the temperature indicated by the camera is the same as the temperature of the object
- Use the reversed temperature measurement formula (Supported by the FLIR A20 Camera)

27-Aug-18

Thermal Imaging and Infrared

14

Emissivity Calculation

IREmissCalc <CameraName> <Xpos> <YPos> <Temperature>

The function IREmissCalc uses the reversed formula to determine the emissivity of an object.

Demonstration Code:


- ImageMode set at 0
- ImageType Temperature Float
- IREmissCalc IRCam 50 80 310

27-Aug-18

Thermal Imaging and Infrared

15

Emissivity Calculation



Emissivity

27-Aug-18

Thermal Imaging and Infrared

16

EmissivityMap

An emissivity map is used to give every pixel a different emissivity value.

- **Not using a single emissivity**
- **Used when monitoring different materials in a single image**
- **Emissivitymap is a DoubleImage with the same size as the infrared snapshot.**

27-Aug-18

Thermal Imaging and Infrared

17

EmissivityMap

IRSetEmissMap <CameraName> <EmissMap>

The function sends an emissivitymap to the camera.

Demonstration Code


- **Create a new DoubleImage with the same size as the IR Image**
- **Enter pixel values between 0.01 and 1**
- **IRSetEmissMap IRCam EmissMask**

27-Aug-18

Thermal Imaging and Infrared

18

EmissivityMap



27-Aug-18

Thermal Imaging and Infrared

19


EmissivityMap

- **Create an EmissivityMap first**
- **IRSetEmissMap**
- **Camera setparam IRCam EmissivityCorrection 0**
Standard global Emissivity value will be used
- **Make a snapshot**
- **Camera setparam IRCam EmissivityCorrection 1**
IR Camera is using the Emissivitymap just created
- **Make a snapshot**

27-Aug-18

Thermal Imaging and Infrared

20



TemperatureMap

A TemperatureMap is used to calculate emissivity values in an image.

The TemperatureMap

- An image of an arbitrary size
- Every pixel contains the known temperature of the pixel in the infrared image
- The same as IREmissCalc only then for multiple pixels
- Returns an image with the emissivity values

Calculating will take some time, the whole image would take approximately 25 minutes.

TemperatureMap

**IRTemperatureMap <CameraName> <TemperatureMap>
<ReturnEmissivityMap> <Left> <Top> <Width> <Height>**

The function uses the camera to calculate multiple emissivity values for known temperature pixels. The return value is an image.

Demonstration Code

- Create a new FloatImage of 50 x 50 pixels
- Enter known pixel temperatures
- **IRTemperatureMap IRCam TemperatureMap EmissivityMap 10 10 50 50**
- **Display EmissivityMap**


27-Aug-18

Thermal Imaging and Infrared

23

TemperatureMap


TemperatureMap image



27-Aug-18

Thermal Imaging and Infrared

24



Experiments

Measuring the temperature of shiny objects
(Objects with a high emissivity)

3 methods

- **Masking Tape**
 - Masking tape has a higher emissivity.
- **Sanding**
 - Reducing the amount of reflection of shiny objects.
- **Drilling a hole with a depth of 7 times its diameter**
 - Simulating a blackbody

27-Aug-18 Thermal Imaging and Infrared 26

Experiment Masking Tape



27-Aug-18

Thermal Imaging and Infrared


27

Experiment Masking Tape


Order of temperature from left to right.

- Hot
- Room temperature
- Cold.

Masking tape is on the top half.



Immediately





after a few minutes

- Normal background

27-Aug-18

Thermal Imaging and Infrared

28



Experiment Masking Tape Hot Background

27-Aug-18

Thermal Imaging and Infrared



31

Experiment Masking Tape Hot Background

Order of temperature from left to right.

- Cold
- Room temperature
- Hot.

Masking tape is on the bottom half.



**Immediately****after a few minutes**

- Hot background

27-Aug-18

Thermal Imaging and Infrared

32



Experiment Sanded



27-Aug-18

Thermal Imaging and Infrared

35

Experiment Sanded**Materials from left to right**

- Red Copper
- Brass




1. Sanded.
2. Not Sanded.

27-Aug-18

Thermal Imaging and Infrared

36



Fields of usage


Kwantitative measurement (Measuring absolute temperatures)

- Not used a lot, due to the complex nature of temperature measurement

Kwalitative measurement (Measuring relative temperatures)

- Electrical Engineering
- Mechanical engineering
- Building inspections
- Many other fields

27-Aug-18 Thermal Imaging and Infrared 38


**Examples
(Infrared reflection)**

Images provided by MapTools B.V.

27-Aug-18

Thermal Imaging and Infrared

39


**Examples
(Building Inspection)**

Images provided by MapTools B.V.

27-Aug-18

Thermal Imaging and Infrared

40


**Examples
(Building Inspection)**

Images provided by MapTools B.V.

27-Aug-18

Thermal Imaging and Infrared

41


**Examples
(Electrical Engineering)**

Images provided by MapTools B.V.

27-Aug-18

Thermal Imaging and Infrared

42


**Examples
(Electrical Engineering)**

Images provided by MapTools B.V.

27-Aug-18

Thermal Imaging and Infrared

43

**Examples
(Mechanical Engineering)**

Images provided by MapTools B.V.

27-Aug-18

Thermal Imaging and Infrared

44

Advantages and Disadvantages

Advantages

- **Quick measurement of object temperature**
- **Non invasive measurement**
- **Ability to use Computer Vision techniques for automating temperature measurement**

Disadvantages

- **Kwantitative measurement depends on al lot of parameters**
 - **Emissivity**
 - **Atmosphere Temperature**
 - **Object material**
- **Expensive equipment**

27-Aug-18

Thermal Imaging and Infrared

45