



Computer Vision

Linear filters (Convolution)

10 April 2018

Copyright © 2001 – 2018 by
NHL Stenden Hogeschool and Van de Loosdrecht Machine Vision BV
All rights reserved

j.van.de.loosdrecht@nhl.nl, jaap@vdlmv.nl

Linear filters

Overview:

- Convolution algorithm
- Low pass filter
- High pass filter
- Sharpening
- Introduction to edge detection

27-aug-18

Linear filters

2

Convolution

Convolution (src, dest, divideFactor, edge, mask)

The convolution operator initialises a destination image by sliding a mask across a source image.

The pixel values under the mask are multiplied by the corresponding maskvalue. All products are summed and the sum is divided by a division factor.

This new value is assigned to the destination image at the position of the centre (= origin) of the mask.

Convolution is a linear filter.

27-aug-18

Linear filters

3


Example with 3x3 mask and origin in centre

First pixel, first row


mask



source image





destination image



27-aug-18

Linear filters

4



Convolution Algorithm for 3x3 mask

Convolution (src, dest, divideFactor, edge, mask)

```
for (h = 1; h < height-1; h++) {  
    for (w = 1; w < width-1; w++) {  
        dest(w,h) = (mask(0,0) * src(w-1,h-1) +  
                    mask(0,1) * src(w,h-1) +  
                    mask(0,2) * src(w+1,h-1) +  
                    mask(1,0) * src(w-1,h) +  
                    mask(1,1) * src(w,h) +  
                    mask(1,2) * src(w+1,h) +  
                    mask(2,0) * src(w-1,h+1) +  
                    mask(2,1) * src(w,h+1) +  
                    mask(2,2) * src(w+1,h+1) ) / divideFactor;  
    } // for w  
} // for h
```

27-aug-18

Linear filters

7

Example with 3x3 mask and origin in centre


What to do with not-initialised border pixels in destination image?

- copy from source image
- set to zero
- remove from image
- extend border of image prior to operation

27-aug-18

Linear filters

8

Exercise John Conway's Game of Life (*)**Rules:**

1. Any live cell with fewer than two live neighbours dies, as if by loneliness.
2. Any live cell with more than three live neighbours dies, as if by overcrowding.
3. Any live cell with two or three live neighbours lives, unchanged, to the next generation.
4. Any dead cell with exactly three live neighbours comes to life.

27-aug-18

Linear filters

9

Exercise John Conway's Game of Life (*)**Write script using framework:**

```

Create gol ByteImage 256 256
Noise gol 6 1 1
SetLut gol Binary
while true
  Convolution gol gol2 1 EdgeExtend 3 3 1 1 1 1 1 1 10 1 1 1 1
  ThresholdMulti gol2 .....
  Display gol2
  Copy gol2 gol
endwhile

```

See gol_framework.jls for framework
 See gol.jls for answer

27-aug-18

Linear filters

10

Low pass filter

Mask (in general):

- mask values ≥ 0
- division factor = sum mask values

Examples:

- smooth mask:

```
1 1 1
1 1 1
1 1 1
```

- gaussian 5x5 mask:

```
1 2 3 2 1
2 7 11 7 2
3 11 17 11 3
2 7 11 7 2
1 2 3 2 1
```

27-aug-18

Linear filters

11

Low pass filter

Usage:

- removal of high frequencies
- noise removal

27-aug-18

Linear filters

12

Demonstration low pass filter


- Open image circles.jl
- Convolution with smooth mask use EdgeExtend
- Analyse pixels on circles.jl and convolution result
 - explain spatial frequency
 - smooth is low pass filter, it eliminates the high frequencies
- Convolution with gaussian 5x5 is a stronger low pass filter (no slides)
- Demo use of own defined masks and parameters (no slides)

27-aug-18

Linear filters

13


Convolution with smooth mask use EdgeExtend



27-aug-18

Linear filters


14

Convolution with smooth mask use EdgeExtend

27-aug-18

Linear filters

15

original**after convolution with smooth**

27-aug-18

Linear filters

16

Demonstration noise reduction

Open image circles.jl


- Add noise 1 0 50 (from Synthetic menu)
- Set display LUTs to clip
- Remove noise with convolution with gaussian 3x3
- Remove noise with convolution with gaussian 5x5, more noise removed but 'softer'

27-aug-18

Linear filters

17


Add noise



27-aug-18

Linear filters


18

Remove noise with convolution with Gaussian 3x3

27-aug-18

Linear filters

19

Remove noise with convolution with Gaussian 3x3

27-aug-18

Linear filters

20

Gaussian Filter

GaussianFilter (image, sigma, size)

This is a generalised implementation of a Gaussian smoothing filter.

Parameters:


- **sigma** is the standard deviation. Typical values are $[2/3 .. 3]$
- **size** is the size of the neighbourhood of the operation. If size is 0 the algorithm calculates a size so that pixels at $3 \cdot \text{sigma}$ are neglected.

27-aug-18

Linear filters

21


Demonstration Gaussian Filter 3 0



27-aug-18

Linear filters

22

Exercise 1 Gaussian filter


- Use image `carpet.jl`
- Try to find the dirty spots in the carpet.

• answer: `carpet.jls`

27-aug-18

Linear filters

23

Exercise 2 Gaussian filter

- Use image `shading_c.jl`
- Try first to segment the image using Threshold
- Then generate a background image using Gaussian and subtract the background before thresholding

• answer: `gaussian2.jls`

27-aug-18

Linear filters

24

High pass filter

Mask (in general):

- centre values > 0
- ring values < 0
- border values $= 0$
- sum values $= 0$
- division factor $= 1$

Examples:

- Laplacian 3x3:

-1	-1	-1
-1	8	-1
-1	-1	-1

27-aug-18

Linear filters

25

High pass filter

Examples (continued):

- Laplacian 5x5:

0	0	-1	0	0
0	-1	-2	-1	0
-1	-2	16	-2	-1
0	-1	-2	-1	0
0	0	-1	0	0

Usage:

- high pass filter
- edge detection, but sensitive to noise

27-aug-18

Linear filters

26

Demonstration high pass filter

- Open image circles.jl
- Convolution with Laplacian 3x3
- 2x analyse pixels:
 - low frequencies -> 0
 - high frequencies -> |pixel value| >> 1
- Convolution with Laplacian 3x3 on image with noise 1 0 50
- Note: noise is amplified
- Can be used as edge detection: Threshold 40 10000 see next example


- Convolution Laplacian 5x5 on circles
- Threshold 40 10000 gives sharp edges

27-aug-18

Linear filters

27



Convolution with Laplacian 3x3




27-aug-18

Linear filters

28



Edge detection: convolution with Laplacian 5x5 succeeded by threshold 40 10000



Sharpening (*)

- Variant of high pass filter sharpening:
Laplacian but original image is 'added' to result
- Mask:

1	1	1	(inverted Laplacian + '1')
1	-7	1	
1	1	1	
- Digital variant of dark room technique in use by TV and video recorder

Demonstration sharpening (*)


- Open image circles.jl
- Convolution with sharpening mask
- Convolution with Laplacian 3x3
- Add original to laplacianed image
- Explain small difference due to division factor
- Dark room technique:
 - Divide result convolution with Laplacian3x3 by pixel value 5
 - Add it to original image

27-aug-18

Linear filters

33


Convolution with sharpening mask (*)



27-aug-18

Linear filters


34

Divide result convolution with Laplacian3x3 by pixel value 5 (*)

27-aug-18

Linear filters

35

Add it to original image (*)

27-aug-18

Linear filters

36

Exercise sharpening (*)

Make a script which sharpens the image
 (optional: add this script as an operator to the system)

The script should accept three parameters (image, result_image and divide factor) perform the operations and display the result

Answer: sharpen.js and sharpen.ini

27-aug-18

Linear filters

37

Mexican hat (*)

- **Combination of low and high pass filter**
- **A Laplacian smoothed by a Gaussian**
- **Mask (7x7):**

0	0	-1	-1	-1	0	0
0	-1	-3	-3	-3	-1	0
-1	-3	0	7	0	-3	-1
-1	-3	7	24	7	-3	-1
-1	-3	0	7	0	-3	-1
0	-1	-3	-3	-3	-1	0
0	0	-1	-1	-1	0	0
- **Local noise is smoothed out by low pass filter in centre**

27-aug-18

Linear filters

38


Demonstration Mexican hat (*)

- Open image circles.jl
- Add noise 1 0 50
- Convolution Laplacian 5x5 on noise image
- Convolution Mexican hat on noise image
(smooth noise and enhance high frequencies)

27-aug-18

Linear filters

39

With noise**Mexican hat****Laplacian (*)**

27-aug-18

Linear filters

40

Laplacian of Gaussian (LoG) filter (*)

LoGFilter (image, sigma, size)

This is a generalised implementation of a Mexican hat filter

Parameters:

- **sigma** is the standard deviation. Typical values are [2/3 .. 10]
- **size** is the size of the neighbourhood of the operation. If size is 0 the algorithm calculates a size so that pixels at $3 \times \text{sigma}$ are neglected

27-aug-18

Linear filters

41

Difference of Gaussians (DoG) filter (*)

DoGFilter (image, sigmaLow, sigmaHigh, size)

An alternative implementation for a generalised Mexican hat filter, using the difference of two Gaussians with substantially different sigmas.

Parameters:

- **sigmaLow** and **sigmaHigh** are the standard deviations for the DoG operator. Typical values are [0 .. 10].
For good approximation Mexican hat of the ratio $\text{sigmaHigh}:\text{sigmaLow}$ should be 1.6:1.
- **size** is the size of the neighbourhood of the operation. If size is 0 the algorithm calculates a size so that pixels at $3 \times \text{sigma}$ are neglected

27-aug-18

Linear filters

42

Edge detection

Mask (in general):

- centre value = 0
- sum of values = 0
- division factor = 1

Examples:

- Sobel NS:

-1	-2	-1
0	0	0
1	2	1

27-aug-18

Linear filters

43

Edge detection

Examples (continued):

- Sobel WE:

-1	0	1
-2	0	2
-1	0	1

Introduction to the next chapter about edge detection

27-aug-18

Linear filters

44

Demonstration edge detection


- Open image edgetest.jl (do not use image sq2.jl)
- Show with edit pixel values of image
- Convolution with SobelINS mask
- Show with edit pixel values of result
- Show mask without executing convolution
- Explanation:
 - transitions from 0 (up) to 10 (down) gives positive values
 - transitions from 10 (up) to 0 (down) gives negative values
 - transitions from left to right and vs. give zeros

27-aug-18

Linear filters

45

Image edgetest.jl




27-aug-18

Linear filters

46

Convolution with SobelINS mask



27-aug-18

Linear filters

47

Demonstration edge detection


- Open image circles.jl
- Convolution with SobelINS mask
- Analyse pixels:
 - horizontal edges are strong
 - vertical edges are weak
- Threshold 100 -100 to show the edges
- Convolution with SobelWE mask on circles for vertical edges

27-aug-18

Linear filters

48

Convolution with SobelINS mask




27-aug-18

Linear filters

49

Threshold 100 -100 to show the edges



27-aug-18

Linear filters

50

